

Item		LEVI350T
General	Screen Size	3.5 Inch
	Resolution	320*240
	Color	65536 color
	Brightness	300 cd/m ²
	Backlight	LED
	Touch Screen	High precision four-wire resistive
	Backlight Life	50000 hours
	CPU	32-bits 400MHz RISC
	Storage	128M FLASH + 64M DDRAM
	RTC	256KB
	Printer Port	USB printer/ Serial port Printer
	USB Port	USB Host + USB Client
	COM	COM1
COM2		
Power	Power	< 5W
	Power Supply	DC 24V (12 ~ 28V DC)
	Allowed Power Fail	< 5ms
	Insulation Resistance	> 20MΩ 500VDC
	Withstand Voltage	500V AC <1 minute
Dimension	Shell	ABS, Black
	Dimension (mm)	96.0W*81.0H*37.0D
	Mounting size (mm)	91.0W* 73.0H
Operate Environment	Temperature	Working Temperature:-10 ~ 60°C; Storage Temperature:-20 ~ 70°C
	Humidity	Working humidity:10 ~ 90%RH; Storage humidity:10 ~ 90%RH
	Seismic Resistance	10 ~ 25 Hz (X, Y, Z direction 2G/30 minutes)
	Cooling	Air cooling
Protection		IP65 (Front panel)
CE Certification		EN61000-6-2:2005, EN61000-6- 4:2007 Standard
FCC Certification		FCC Class A
Programming Software		LeviStudioU (FREE)